



Cat# 71440
LED Classic Large Wall-Pack



Model :		71440
OVERALL LAMP PARAMETERS	Input Voltage	100-277VAC
	Input Current	.98@120VAC, .90@277VAC
	Input Power	121W
	Power Factor	PF≥0.9
	Luminance	12333LM
	Luminous Efficiency	101LM/W
	CRI	83
	Beam Angle	114.8°
	Main Structure	Alluminium + Tempered Glass
	Surface	Baking Varnish
LED DRIVER	Output Voltage	25.2-42VDC
	Output Current	1.2A
	Driver Efficiency	88%
LED	LED Type	LUMILED LUXEON 3030
	LED Quantity	100 PCS
	LED Manufacturer	philips
	LED Efficacy	140 lm/W
	Color Temperature	4983K
LIFESPAN & ENVIRONMENT	Lifespan	50000 Hrs.
	Warranty	5 Years
	IP Rating	IP65
	Operating Temperature	-40°F—+131°F
	Storage Temperature, Humidity	-40°F—+176°F, 10—90% RH
SAFETY&EMC	Safety Norms	EN60598, EN61347-2-13, EN62031, EN62471, UL1598, UL8750
	Withstand Voltage	I/P-FG: 2121VDC
	Grounding Resistance	25A 100mΩ
	Electromagnetic Compatibility	EN55015, EN61000-2-3, EN61000-3-3, EN61547
	DLC	DLC Listed Only When Full Cutoff Visor is Installed
OTHERS	Dimension	Pls refer to attached dimension drawing
	Net Weight(Kg)	4.3
	Gross Weight(Kg)	5.2
	Box Size	--
	Carton Size	390*230*315
	Q'ty / Carton	1

Dimension: 71440

